



DECKSHIELD

Multi-Story Parking Deck Systems

- ✓ Basement Decks
- ✓ Intermediate Decks
- ✓ Exposed Decks
- ✓ Turning Circles
- ✓ Stairwells
- ✓ Color Zoning



Welcome to Flowcrete Americas

Flowcrete is a world leader in the manufacture of seamless resin flooring systems for application in both industrial and commercial environments.

Flowcrete Americas has a fresh approach to flooring and is constantly looking to introduce world-class systems, which offer clients a number of performance advantages while at the same time make floors much more than a surface to walk on.

Flowcrete Americas is dedicated to innovating sustainable flooring materials and using the earth's natural resources responsibly across all operations to ensure a more positive impact on the construction industry and a greener world at our feet.

The company's headquarters in Texas serves expanding business opportunities across the continent including the USA, Canada, Latin America and the Caribbean. With key clients including Coca Cola, L'Oréal, Cargill, Nestlé, NASA, GE and Southwest Airlines, Flowcrete Americas continues to develop a significant presence in the Americas' polymer flooring market.

Flexible Deck Coating Systems for Parking Structures



Parking structures have a crucial role to play as the first point of call for a visitor to any public, private or commercial building.

The parking area is the 'front door' of the building, while serving its essential primary functional role. There is no doubt that first impressions count and appearance, ease of use, signage, bright lighting and clear directional marking all help to make a parking zone a more positive and safer environment.

By utilizing the very best of protective coating systems on the internal structure of the parking area, visual appearance can be enhanced, light reflectivity can be improved, traffic movement can be regulated and ongoing structural maintenance can be kept to an absolute minimum.



Performance Benefits

✓	Bright and attractive finishes
✓	Reduces noise from tire squeal
✓	Wear and abrasion resistant
✓	Crack-bridging
✓	Solvent free
✓	Fire resistant
✓	Flexible waterproof membrane

Deckshield Application Suitability



Basement
Decks




Intermediate
Decks



Exposed
Decks



Ramps &
Turning Circles




Stairwells &
Corridors



Color Zoning

Forces Impacting on the Multi-Story Parking Structure



Deckshield ID (40 mils)

A flexible polyurethane deck coating system for use on intermediate decks of multi-story parking structures.

Deckshield ID cosmetically enhances multi-story parking environments and ensures safety underfoot with enhanced traction.



UV Resistant:

100% UV stable formulation available to prevent the floor from yellowing.



Slip Resistant:

Positively textured anti-slip surface minimizes slip and skid risks.



Chemical Resistant:

Protects against diesel, fuel, antifreeze, hydraulic fluid, chlorides and battery acid.



Noise Reducing:

Enhanced traction underfoot minimizes unpleasant noise from tire squeal.



Low Odor:

Solvent-free & low VOC formulation with low odor installation even in confined areas.

Standard Colors:



Blue




Red



Green



Mid Gray



Dark Gray




Black

The applied colors may differ from the examples shown. For a full color chart and samples, contact your local Flowcrete office.


Technical Profile

COMPRESSIVE STRENGTH:			
ASTM C 579	10,500 psi		
TENSILE STRENGTH:			
ASTM C 307	1,600 psi		
FLEXURAL STRENGTH:			
ASTM C 580	4,200 psi		
SLIP RESISTANCE:			
(PTV) Method described in BS 7976-2 (typical values for TRRL rubber slider)	Dry 92 Wet 46		
ABRASION RESISTANCE:			
ASTM D 4070 CS 17 Wheel, 1000 Cycles	0.050g loss		
VAPOR PERMEABILITY:			
Karsten Test	Nil (impermeable)		
BOND STRENGTH:			
Greater than cohesive strength of 3,000 psi concrete, > 220 psi			
FIRE RESISTANCE:			
BS 476-3	Designated EXT.FAA		
VOC:			
50 g/l			
SPEED OF CURE:			
	50°F	70°F	90°F
Light Traffic	36 hrs	10 hrs	10 hrs
Full Traffic	72 hrs	36 hrs	24 hrs
Full Chemical Cure	7 days	3 days	48 hrs



Application Suitability

Basement Decks	✓
Intermediate Decks	✓
Exposed Decks	
Ramps & Turning Circles	✓
Stairwells & Corridors	✓
Color Zoning	✓
Service Corridors	



Deckshield Rapide ID (60 mils)

A fast cure MMA deck coating system for use on intermediate decks of multi-story parking structures.

Deckshield Rapide ID ensures quick and speedy install over large areas in order to minimize any operational downtime to the structure.



Fast Cure:

Accelerates cure time, providing a fully operational surface in just 60 minutes.



Slip Resistant:

Positively textured anti-slip surface minimizes slip and skid risks.



Chemical Resistant:

Protects against diesel, fuel, antifreeze, hydraulic fluid, chlorides and battery acid.



UV Resistant:

100% UV stable formulation available to prevent the surface from yellowing.



Noise Reducing:

Enhanced traction underfoot minimizes unpleasant noise from tire squeal.

Standard Colors:



Blue



Brick Red



Green



Light Gray




Medium Gray



Dark Gray

Technical Profile

COMPRESSIVE STRENGTH (SEALER):			
ASTM C 579	11,600 psi		
TENSILE STRENGTH (SEALER):			
ASTM C 307	2,900 psi		
FLEXURAL STRENGTH (SEALER):			
ASTM C 580	4,350 psi		
SLIP RESISTANCE:			
(PTV) Method described in BS 7976-2 (typical values for TRRL rubber slider)	Dry 80 Wet 60* (slip profile)		
ABRASION RESISTANCE (TOP COAT):			
ASTM D 4060 CS17 Wheel, 1000 cycles	0.080g loss		
IMPACT RESISTANCE:			
ISO6272	2.2 lb weight > 70 in 4.4 lb weight > 59 in		
VAPOR PERMEABILITY:			
Karsten Test	Nil (impermeable)		
BOND STRENGTH:			
Greater than cohesive strength of 3,000 psi concrete, > 220 psi			
FIRE RESISTANCE:			
BS 476-3	Designated EXT.FAA		
VOC:	50 g/l		
SPEED OF CURE:	32°F	70°F	90°F
Light Traffic	60 mins	45 mins	45 mins
Full Traffic	90 mins	60 mins	60 mins
Full Chemical Cure	120 mins	90 mins	90 mins



The applied colors may differ from the examples shown. For a full color chart and samples, contact your local Flowcrete office.

Deckshield Rapide ED (100 mils)

A fast cure MMA deck coating system for use on external or exposed decks of multi-story parking structures.

Deckshield Rapide ED ensures quick and speedy install over large areas in order to minimize any operational downtime to the structure.



Fast Cure:

Accelerates cure time, providing a fully operational surface in just 60 minutes.



Slip Resistant:

Positively textured anti-slip surface minimizes slip and skid risks.



Chemical Resistant:

Protects against diesel, fuel, antifreeze, hydraulic fluid, chlorides and battery acid.



UV Resistant:

100% UV stable formulation available to prevent the surface from yellowing.



Noise Reducing:

Enhanced traction underfoot minimizes unpleasant noise from tire squeal.

Standard Colors:



Blue




Red



Green



Mid Gray



Dark Gray



Black

Technical Profile

COMPRESSIVE STRENGTH (SEALER):

ASTM C 579	11,600 psi
------------	------------

TENSILE STRENGTH (SEALER):

ASTM C 307	2,900 psi
------------	-----------

FLEXURAL STRENGTH (SEALER):

ASTM C 580	4,350 psi
------------	-----------

SLIP RESISTANCE:

(PTV) Method described in BS 7976-2 (typical values for TRRL rubber slider)	Dry 80 Wet 60* (slip profile)
---	----------------------------------

ABRASION RESISTANCE (TOP COAT):

ASTM D 4060 CS17 Wheel, 1000 cycles	0.080g loss
--	-------------

IMPACT RESISTANCE:

ISO6272	2.2 lb weight > 70 in 4.4 lb weight > 59 in
---------	--

VAPOR PERMEABILITY:

Karsten Test	Nil (impermeable)
--------------	-------------------

BOND STRENGTH:

Greater than cohesive strength of 3,000 psi concrete, > 220 psi

FIRE RESISTANCE:

BS 476-3	Designated EXT.FAA
----------	--------------------


TEMPERATURE RESISTANCE:

Softens over 158°F, hardens on cooling

VOC:	50 g/l
------	--------

SPEED OF CURE:

	32°F	70°F	90°F
Light Traffic	60 mins	45 mins	45 mins
Full Traffic	90 mins	60 mins	60 mins
Full Chemical Cure	120 mins	90 mins	90 mins



* Typical value is dependant on aggregate used.



Flowcrete Group

Flowcrete Group is the world's leading specialist in seamless resin floor, wall and coving solutions as well as other specialist coating technologies with operations on six continents.

Europe & Middle East

Baltic States	+48 883 303 880	latvia@flowcrete.com
Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Germany	+49 4187 50 29 470	germany@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 64 86 08 30	norway@flowcrete.com
Poland	+48 22 879 89 07	poland@flowcrete.com
Romania	+48 883 303 880	romania@flowcrete.com
Russia	+7 495 645 83 18	rus@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 327 97 97	turkey@flowcrete.com
UAE	+971 4 886 4728	uae@flowcrete.com
UK	+44 1270 753 000	uk@flowcrete.com

Africa

East Africa	+254 20 682 1011	eastafrica@flowcrete.com
South Africa	+27 31 461 3411	southafrica@flowcrete.com

India

India	+91 44 4202 9831	india@flowcrete.com
-------	------------------	---------------------

Asia Pacific

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+88 02 9857222	bangladesh@flowcrete.com
China	+86 10 8472 1912	china@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Malaysia	+60 3 6277 9575	malaysia@flowcrete.com
Philippines	+63 917 514 2696	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 8 6287 0846	vietnam@flowcrete.com

Americas

Brazil	+55 11 3230 1107	brazil@flowcrete.com
Canada	+1 800 218 1850	canada@flowcrete.com
Chile	+56 2 2938 1962	chile@flowcrete.com
Colombia	+57 1 381 9254	colombia@flowcrete.com
Mexico	+01 800 099 0468	mexico@flowcrete.com
USA	+1 936 539 6700	usa@flowcrete.com

*Whilst every care has been taken to ensure that the information included in this document was accurate at the time of printing, Flowcrete reserves the right to change product specifications at any time without prior notice. The photographs and colours reproduced in this publication are within the constraints of the printing process and are not to be used for matching purposes. All photographs are used for approximate representation only and may not show the actual products on offer. E&OE.